

## Differential pressure switches – Robust construction

Instrument Model	Sensor and Material	Range	On-off Differential	Max. Working Pressure	Contact Rating
<b>301 / 304</b>	<b>Metallic Diaphragm</b> 316LSS / Monel	3 – 25 mbar to 1.5 – 15 bar	Fixed	110 / 250 bar	5A / 15A 250V AC
<b>303</b>	<b>Metallic Diaphragm</b> 316LSS / Monel	5 – 120 mbar to 0.1 – 1.5 bar	Adjustable	110 bar	15A 250V AC
<b>381</b> (Dual Setpoint)	<b>Metallic Diaphragm</b> 316LSS / Monel	3 – 25 mbar to 0.7 – 7 bar	Fixed	110 bar	5A / 15A 250V AC
<b>384</b> (Dual Setpoint, High Static Pressure)	<b>Metallic Diaphragm</b> 316LSS / Monel	3 – 25 mbar to 0.7 – 7 bar	Fixed	250 bar	5A / 15A 250V AC
<b>306</b> (Low Ranges)	<b>Diaphragm</b> Nitrile	(-)2.5 – (+)2.5 mbar to 0.2 – 4 bar	Fixed	Upto 15 bar	5A / 15A 250V AC
<b>386</b> (Dual Setpoint Low Ranges)	<b>Diaphragm</b> Nitrile	5 – 120 mbar to 0.2 – 4 bar	Fixed	15 bar	15A 250V AC
<b>310</b> (Very Low Ranges)	<b>Diaphragm</b> Neoprene / EPDM / Silicone / Nitrile	(-)2.5 – (+)2.5 mbar to 10 – 100 mbar	Fixed	0.5 bar	5A / 15A 250V AC
<b>313</b> (Very Low Ranges)	<b>Diaphragm</b> Neoprene / EPDM / Silicone / Nitrile	0.5 – 5 mbar to 10 – 100 mbar	Adjustable	0.5 bar	15A 250V AC

## Differential pressure switches – OEM Series

Instrument Model	Sensor and Material	Range	On-off Differential	Max. Working Pressure	Contact Rating
<b>DM 301 / 304</b> (Compact)	<b>Diaphragm</b> 316LSS / Nitrile	3 – 25 mbar to 1.5 – 15 bar	Fixed	110 / 250 bar	5A / 15A 250V AC
<b>DM 303</b> (Compact)	<b>Diaphragm</b> 316LSS	5 – 120 mbar to 1.5 – 15 bar	Adjustable	110 bar	15A 250V AC
<b>DM 361 / 363</b> (Low Ranges Compact)	<b>Diaphragm</b> Nitrile	(-)2.5 – (+)2.5 mbar to 0.2 – 4 bar	Fixed / Adjustable	Upto 15 bar	5A / 15A 250V AC

**GM – 301**



**DM – 303**



**GN – 310**



**GR – 301**

